

Super Wax Stripper

Caution

Keep Out Of Reach Of Children. See Side Panel For Additional Precautionary Statements.

Net Contents:

FOR SAFE, EFFICIENT REMOVAL OF OXIDIZED AND WORN FLOOR FINISHES. ALL-PURPOSE—REMOVES CARNAUBA WAX, ACRYLICS AND METALLIC CROSS-LINKED FINISHES.

GENERAL INFORMATION:

Super Wax Stripper is formulated to provide the chemical action to penetrate, emulsify and remove all types of floor finishes from asphalt tile, vinyl and vinyl asbestos tile, rubber tile, cork, linoleum, ceramic tile, terazzo and marble.

DIRECTIONS FOR USE:

Remove as much loose dirt and soil as possible from the floor by thoroughly sweeping. If corners and baseboards have very heavy build up of old finish, dilute one part of Super Wax Stripper with one part of very hot water and apply liberally to these areas with a mop or a brush. Then dilute one part of Super Wax Stripper with ten parts of water (hot water will speed up stripping action) and apply this solution to the area to be re-finished. Allow solution to remain on the floor for approximately five minutes or until old finish is softened, and then pick up with mop or automatic scrubbing machine. Do not work on an area so large that solution has time to dry. For badly soiled or oxidized finishes, it may be necessary to use a strong solution - one part Super Wax Stripper to five parts of hot water. When old finish has been completely removed, use a vinegar and water rinse followed by a plain water rinse to be certain all of the stripper and old finish has been removed. After the floor is thoroughly dry, it is ready for floor finish.

DIRECCIONES:

Barra bien el piso quitando toda la basura y tierra. Para esquinas y molduras que tienen acumulacion de polvo mezcle una parte de Super Wax Stripper con una parte de agua caliente y aplique estas areas con un cepillo o mechon. Luego mezcle una parte de Super Wax Stripper con diez partes de agua (agua caliente lo limpia mas rapido) y aplique esta solucion a la area que desea retocar. Deje reposar la solucion por 5 minutos o hasta que este blando. Levantelo con un mapeador (mechon) o una maquina automatica limpiasuelos. Limpie espacios chicos para no dar tiempo que la solucion se seque. Para areas muy sucias y oxidadas va ser necesario usar mezclas mas fuertes. Una solucion de Super Wax Stripper a 5 partes de agua caliente. Despues de que quite completamente lo sucio y oxidado, limpie una o dos veces con aqua pura.

Batch#:

CAUTION:

Contains Potassium Hydroxide (CAS #1310-58-3), Dipropylene Glycol Monomethyl Ether (CAS #34590-94-8), Monoethanolamine (CAS #14-43-5), and Sodium Metasilicate (CAS #8834-92-0). DELIBERATE INHALATION OF VAPORS CAN CAUSE D

EMERGENCY AND FIRST AID PROCEDURE:

EYES: Immediately flush with plenty of water for at least 15 minutes. Hold eyelids open during flushing. Call a physician or poison center immediately.

SKIN: Flush area with water while removing contaminated clothing. Follow by washing with soap and water. If irritation persists, call a physician or poison center.

INHALATION: Remove to fresh air. Apply artificial respiration if needed. If irritation persists, call a physician.

INGESTION: DO NOT induce vomiting. Contains potassium hydroxide, glycol ethers and strong alkalis. Give plenty of water. Never give anything by mouth to an unconscious person. Consult a physician or poison center immediately.

An MSDS for this product is available through AMRO's website at www.amroproducts.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS: SPECIFIC HAZARDS:

HEALTH-3 FLAMMABILITY-0 PHYSICAL HAZARD-0 HMIS* III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Gloves & Goggles

Made and Printed in U.S.A

2NB16-13